



WÜRTH

TRIATHLON OILS

For Engine & Transmission

**#READY
FOR WORK**

Engine oil TRIATHLON® Synth A 5W-50

Smooth-running engine oil for top-performance passenger cars

TRIATHLON® engine oils are produced and packaged in compliance with the most stringent quality specifications in accordance with DIN EN ISO 9001

- The latest technology combination of unconventional synthetic-based oils using advanced additive technology ensures high shear stability for the motor oil.
- Reliably prevents the formation of deposits
- Reducing frictional loss in the engine
- Providing the optimal protection from wear.
- Optimal for modern passenger vehicles with gasoline and diesel engines with and without turbochargers and with and without charge air cooling.
- Especially suitable where there are heavy duty engine requirements.



Type of oil	Fully Synthetic
Viscosity grade	5W-50
Approved for engine oils	API SM/CF ACEA A3/B4
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
4L	0897105542	4

Application

Ideally suited for petrol and diesel engines including vehicles with diesel particulate filters in accordance with Euro IV, Euro V and Euro VI emission standard.

Approvals/Recommendations

- MB approval 229.3
- VW 502 00, 505 00
- BMW Longlife-98
- Porsche A40

Engine oil TRIATHLON® Power 5W-40

Smooth-running engine oil for top-performance passenger cars

TRIATHLON® engine oils are produced and packaged in compliance with the most stringent quality specifications in accordance with DIN EN ISO 9001

- Smooth-running engine oil for optimum engine performance.
- Excellent wear protection for a longer engine service life.
- Saves fuel and reduces emissions.
- Outstanding corrosion protection and low-temperature performance. Can be used down to -30°C .
- Year-round oil for modern gasoline and diesel engines. Especially ideal for the most stringent requirements.
- Tested with turbochargers and catalytic converters.



Type of oil	Fully Synthetic
Viscosity grade	5W-40
Approved for engine oils	API SN/CF ACEA A3/B4
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
4L	0897605406	4
208L	0897605405	1

Application

Ideally suited for petrol and diesel engines including vehicles with diesel particulate filters in accordance with Euro IV, Euro V and Euro VI emission standard.

Approvals/Recommendations

- MB approval 229.3
- VW 502 00, 505 00
- BMW Longlife-98
- Daihatsu
- Honda
- Hyundai
- Kia
- Isuzu
- Mazda
- Mitsubishi
- Nissan
- Suzuki
- Toyota
- Subaru
- GM

Engine oil TRIATHLON® Endurance III 5W-30

Smooth-running engine oil for top-performance passenger cars

Fast oil supply at low temperatures

Oil change intervals from 30,000 to 50,000 km are possible depending on the manufacturer's specifications

HC synthetic

TRIATHLON® engine oils are produced and packaged in compliance with the most stringent quality specifications in accordance with DIN EN ISO 9001

- High level of product safety
- Comprehensive manufacturer approvals

Only high-quality first raffinates and raw materials are used for TRIATHLON® oils

Fulfills key specifications of automotive manufacturers



Type of oil	Fully Synthetic
Viscosity grade	5W-30
Approved for engine oils	API SN/CF ACEA C3
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
4L	0897105307	4
208L	0897105305	1

Application

Ideally suited for petrol and diesel engines including vehicles with diesel particulate filters in accordance with Euro IV, Euro V and Euro VI emission standard. Also includes the Volkswagen standards with the exception of R5 and V10 TDI engines before 6/2006

Approvals/Recommendations

- VW 500 00 / 501 01 / 502 00 / 504 00 / 505 00 / 505 01 / 503 00 / 503 01 / 506 00 / 506 01 / 507
- MB 229.31 / 229.51

Engine oil Triathlon® Synth A 0W-30

The latest fully synthetic low-friction motor oil for year-round use

Triathlon® Engine Oils are produced and packaged in compliance with the most stringent quality specifications according to DIN EN ISO 9001

- High level of product safety
- Broad manufacturer approvals

With Triathlon® Oils, only high quality first raffinates and raw materials are used

Fulfills the major specifications of automobile manufacturers.

Synth A 0W-30

The combination of synthetic base oils using advanced additive technology ensures low viscosity and high shear stability for the motor oil and reliably prevents the formation of deposits, reduces frictional loss in the engine and provides optimal protection from wear.



Type of oil	Fully Synthetic
Viscosity grade	0W-30
Approved for engine oils	ACEA A3/B4 API SM/CF
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
4L	0897100306	4

Application

Optimal for modern passenger vehicles with gasoline and diesel engines with and without turbochargers and with and without charge air cooling. Especially suitable where there are heavy duty engine requirements.

Approvals/Recommendations

- BMW Longlife-98
- MB 229.3
- Porsche
- VW 502 00
- VW 505 00

Engine oil Triathlon® SAE 0W-20

Modern premium-class fuel-efficient synthetic engine oil for long oil change intervals and high motor requirements

TRIATHLON Select engine oil is especially developed for the year-round use in Asia and American vehicles.

Guarantees the engine oil to fight against wear, reduce the oil and fuel consumption.

Synthetic base oil technology in connection with the latest additives



Properties:

- Smooth engine running
- Long service life of the engine
- Quick oil supply at low temperatures
- High shear stability
- Reduces fuel consumption as well as pollutant emission
- Excellent engine cleanness
- Tested for turbochargers and catalytic converters

Type of oil	Fully Synthetic
Viscosity grade	0W-20
Approved for engine oils	API SN ILSAC GF-5
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
4L	0897105104	4

Application

Ideal for modern Asian and American gasoline engines. Particularly suitable in case of long oil change intervals and high motor requirements.

Approvals/Recommendations

- Daihatsu
- Honda
- Hyundai
- Kia
- Isuzu
- Mazda
- Mitsubishi
- Nissan
- Suzuki
- Toyota
- Subaru

Engine oil Triathlon® Ultra Base 10W-40

High-performance, low-friction engine oil based on synthetic technology

Triathlon® Engine Oils are produced and packaged in compliance with the most stringent quality specifications according to DIN EN ISO 9001

- High level of product safety
- Broad manufacturer approvals

With Triathlon® Oils, only high quality first raffinates and raw materials are used

Fulfills the major specifications of automobile manufacturers

Ultra Base 10W-40

It is suitable for year-round use in modern petrol and passenger vehicle diesel engines with and without exhaust-gas turbocharging and charge air cooler



Type of oil	Semi Synthetic
Viscosity grade	10W-40
Approved for engine oils	API SM/CF ACEA A3/B3
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
4L	0897610406	4
208L	0897110405	1

Application

Optimum oil for modern petrol and passenger vehicle diesel and turbocharged engines with and without charge air cooling.

Approvals/Recommendations

- VW 500 00
- VW 505 00

Engine oil Triathlon® Select A 5W-30

Modern premium-class fuel-efficient engine oil, which especially has been developed for the year-round use in Asian and American vehicles

Triathlon® Engine Oils are produced and packaged in compliance with the most stringent quality specifications according to DIN EN ISO 9001

- High level of product safety
- Broad manufacturer approvals

With Triathlon® Oils, only high quality first raffinates and raw materials are used

Fulfills the major specifications of automobile manufacturers

Select A 5W-30

- The combination of unconventional base oils on synthesis technology in connection with the latest additives guarantees an engine oil which protects against wear, reduces oil and fuel consumption
- According to the instructions of the manufacturer, oil change intervals of up to 40,000 km are realizable



Type of oil	Semi Synthetic
Viscosity grade	5W-30
Approved for engine oils	API SN ILSAC GF-5
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
4L	0897605306	4
208L	0897605305	1

Application

Ideal for modern Japanese and American gasoline engines. Particularly suitable in case of long oil change intervals and high motor requirements.

Approvals/Recommendations

- Daihatsu
- Honda
- Hyundai
- Kia
- Isuzu
- Mazda
- Mitsubishi
- Nissan
- Suzuki
- Toyota
- Subaru
- GM

Engine oil POWER® Mineral Oil

Smooth-run low friction mineral oil is based on high-grade base oil and selected additive combinations

- Guarantees engine cleanliness, dispersing effect, corrosion prevention and wear protection properties
- Thermal-oxidative stability in keeping with the particular level of performance
- Good viscosity-temperature characteristics and multi-grade features
- Ensures all season use, and the smooth-run
- Minimize fuel consumption



Type of oil	Mineral
Approved for engine oils	API SM/CF ACEA A3/B3 CCMC G5 / PD2 / D4
Shelf life from production	60 Month

Viscosity Grade	Contents	Art. no.	P. Qty.
10W-30	3L	NE60000018	6
10W-30	4L	NE60000019	6
15W-40	4L	NE60000016	6
20W-50	4L	NE60000017	6

Application

Ideally suited for petrol and diesel engines including vehicles with diesel particulate filters in accordance with Euro IV, Euro V and Euro VI emission standard.

Approvals/Recommendations

- Mercedes Benz
- BMW
- Volvo
- Peugeot
- Audi
- VW
- Citreon
- Fiat
- Renault
- Seat
- Honda
- Toyota
- Mazda
- Hyundai
- Mitsubishi
- Suzuki
- Nissan
- Daihatsu

Transmission oil Triathlon® Automatic Super Synthetic Dexron VI ATF Oil

- Gearbox oil for universal use with high thermal stability and excellent synthetic properties
- Outstanding protection against wear and corrosion
- Optimum viscosity and temperature behavior
- Good aging stability



Type of oil	Synthetic
Grade of oil	Dexron VI
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
20L	0897410003	1

Application

Universal use for use in both passenger cars and commercial vehicles. Also suitable for 6-speed transmissions, 8-speed transmissions and 10-speed transmissions.

Approvals/Recommendations

- Dexron VI / Dexron III H/G / Dexron II E/D
- MAN 339 Type V1 / MAN 339 Type Z1
- MB 236.1
- Ford Mercon
- GM Dexron
- Hyundai ATF
- KIA ATF
- Lexus ATF
- Nissan Matic
- Toyota ATF
- ZF-TE-ML 02F / ZF-TE-ML 03D / ZF-TE-ML 09 / ZF-TE-ML 11B / ZF-TE-ML 14B / ZF-TE-ML 04D / ZF-TE-ML 14A / ZF-TE-ML 17C



**#READY
FOR WORK**

TRIATHLON OILS

Würth Malaysia Sdn Bhd
Lot 35, Jalan Delima 1/3,
Subang Hi-Tech Industrial Park,
40000, Shah Alam, Selangor.
T +603 58888 420
M +6012 345 3493
inquiry@wurth.com.my
www.wurth.my

We reserve the right, at any time without prior notice or notice, to make any product changes that we feel necessary. Images may be for illustration purposes only and that might differ in appearance from the delivered goods. All products and items are whilst stock last. We reserve the right for misprints where we assume no liability. The General Terms and Conditions apply.



@wurthmalaysia